

Product DATASHEET

Digital Psychrometer + InfraRed Thermometer

Humidity, Wet bulb, Dew Point, Air Temperature plus IR for Non-contact Temperature measurements

Features:

- Triple display with backlighting
 - View Air temp+RH+surface temp
 - View Dew Point+RH+surface temp
 - View Wet Bulb+RH+surface temp
- InfraRed Thermometer with
 - Built-in laser pointer
 - 8:1 distance to target ratio
 - Adjustable Emissivity from 0.3 to 1.0
- Precision humidity capacitance sensor is retractable for protection during transportation and storage
- Calculates T1 (IR Surface Temperature) - DP (Dew Point) differential
- Programmable Auto power off and Low battery indication
- Over-range/under-range alert indicator
- Built-in RS-232 interface for capturing readings on a PC
- RH401 complete with 4 AAA batteries and carrying case
- Optional RH405 kit includes meter, 33% and 75% calibration bottles, RS-232 cable, 4 AAA batteries and carrying case

Applications:

- Monitor Wet Bulb, Dew Point, Relative Humidity and Temperature in factories, clean rooms, offices, and greenhouses
- Non-contact InfraRed surface temperature measurements in hard to reach areas such as heating and air conditioning duct
- Humidity monitoring in schools, offices and manufacturing or storage areas



RH405 Digital Psychrometer + InfraRed Thermometer Kit includes calibration bottles, RS232 cable, and carrying case.



CE

Specifications	Range	Max Resolution	Basic Accuracy
Humidity:	10 to 90%RH	0.1%RH	±3%RH
InfraRed Temperature	-40 to 932°F (-40 to 500°C)	0.1°	±3%
Air Temperature	-4 to 122°F (-20 to 50°C)	0.1°	±3%
Dew Point	-90.4 to 122°F (-68.0 to 49.9°C)		
Wet Bulb	-6.9 to 122°F (-21.6 to 49.9°C)		
Emissivity	Adjustable 0.3 to 0.99		
Field of View	8:1		
Dimensions/ Weight	6.8x2.7x1.9i (175x70x50mm)/ 4.9oz (140g)		

Ordering Information:

- RH401**Digital Psychrometer + InfraRed Thermometer
RH401-NISTDigital Psychrometer + InfraRed Thermometer w/NIST Cert
RH405Digital Psychrometer + InfraRed Thermometer Kit
RH405-NISTDigital Psychrometer + InfraRed Thermometer Kit w/NIST Cert
44473338% RH calibration reference
44475575% RH calibration reference
589250RS-232 cable

"Make mine an Extech!"
www.extech.com



10/06/04 - R1